# **PSM-CTH**

## CO<sub>2</sub> Temperature and Humidity Sensors



#### **Description**

Stylish ABS housing in choice of colours, with slotted vents for airflow across the sensors. CO2, Temperature and Humidity sensors 3 off 0 -10 outputs.

#### **Specification**

Housing: Flame retardant ABS housing

86mm x 86mm x 25mm

Available in White (RAL9003), Black (RAL9005)

or Grey (RAL7047)

Power supply: 24Vac/dc

CO<sub>2</sub> sensor: Non dispersive Infra-red technology.

> Self calibrating ABC algorithm which monitors and adjusts the calibration (for non continuous occupation applications)

Range: 0 - 2000ppm Output: 0 - 10Vdc

Range: 0 - 40 degC Temperature Sensor Output: 0 - 10Vdc


Humidity Range 0 - 100% (3% accuracy)


Output: 0 - 10Vdc Sensor

LED indication Red / Yellow/ Green LEDs to indicate CO2

(optional) level

Green < 800ppm





### **Associated Products**


CO2 sensors CO2 and Temp sensors BACnet CO<sub>2</sub> sensors

Flush mount CO2 / Temp / Humidity sensors

CO<sub>2</sub> level Indicators







If this product doesn't quite suit your application - Contact us to discuss a bespoke version