

FM1-T

Plate Temperature Sensor

Description

Stylish flat plate sensor housing which can be fitted with a wide choice of sensor options. Standard single gang plate with 5mm deep slotted grid for airflow across the sensor. Available in a wide range of materials and finishes.

Material

Brushed stainless steel, Polished stainless steel, Lacquered Brass, Powder coated in RAL colours. Any plated finish to match existing electrical hardware (See our leaflet for the range of finishes). Also available in any style to match existing Electrical switchplates (eg screwless etc)

Specification

- Plate; 86mm x 86mm
fits standard single gang back box
25mm deep
- Grid; 5mm deep slotted grid . Available in Black or White
- Sensor; Choice of high accuracy NTC Thermistor or Platinum sensors



Ordering information

FM1T - 01 - 01 - 10

Finish	
Ref	Finish
01	Brushed Stainless steel
02	Polished Stainless steel
05	Lacquered Brass
07	Powder coated (state RAL colour)
11	White primer
XX	Match Electrical switchplates (state range and finish) eg Focus SB Ambassador Polished Nickel

Slotted Grid	
Ref	Colour
01	Black
02	White

Sensor Type		
Ref	Sensor	System
01	1.8K3A1	TAC
04	3K3A1	Alerton
10	10K3A1	Trend, Honeywell, Next, Smart
12	10K4A1	Andover, Delta, york
15	20K6A1	Honeywell
20	50K6A1	Priva
30	SAT1	Satchwell
52	PT1000A	Cylon
60	LS Ni1000	Siemens
70	Mitsi	Mitsubishi
72	Daik	Daikin
80	33K6A3	KNX
XX	Other	Specify when ordering

Example:

FM1T- 01 - 01 - 10
Brushed Stainless steel plate, Black grid, 10K3A1 Thermistor

Bold = Standard item available from stock

Associated Products

- Button Sensors
- Discrete Temperature Sensors
- Thimble Temperature Sensors